




# Product features:



- Single lever control for effortless single handed control
- Custom designed for lower range pressures
- Supplied compete with flexible tail pipes for fast simple fitting
- · Swivel aerator connector for maximum flexibility



Packaged properties:


Box length (mm): 395 Box depth(mm): 95

Box width(mm): 165 Boxed weight (Kg): 2.7 Includes pop up waste?: Yes

**Additional comments:** 

Includes black plastic valve removal tool

### **Product dimensions:**



Product mounted where: Surface • Recommended hole size: Ø 35 mm

 Overall Height / projection: 137 mm • Exit reach: 116 mm • Exit height: 95 mm • Base size: 54 x 61 mm


• Inlet centre distance(s):

• Min. fitting depth required:

45 mm

· Max. surface depth:

## **Product flow characteristics:**



- Min / Max water pressure (bar): 0.30\* / 5.00
- Part G max. mixed flow rate at 3 bar (I/m): >16.6
- Inlet connection type / length: Flexible / 420 mm
- Inlet (plumbing connection) / outlet size: 1/2" F / m10
- Product flow characteristics: Single flow Non return valve(s) supplied or position:
- Aerator type: White flow straightener
- Control valve type: Single lever (40mm)
- Includes output diverter?: No
- Inlet meshed particle filters included:
- Shower hose type / length:

## Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year O-rings, hoses & gaskets warranted for 1 year

### Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives